

EPA/CR BlowVac Special

TRULY VERSATILE EPA VACUUM CLEANER / BLOWER WITH ADVANCED CLEANROOM HI-FILTRATION SYSTEM FOR FACTORY CONTRACT CLEANING AND HARD TO REACH DUST & DEBRIS FROM ESD SENSITIVE ELECTRONIC EQUIPMENT, ASSEMBLY LINES, R&D AREA'S AND IN FIELD-SERVICE.

- ✓ CONTROLLED SOFT (SR : 10E7 - 10E8 OHMS/SQ.) ESD-SAFE STATIC DISCHARGE FROM HOUSING AND VACUUM NOZZLES TO EARTH POWER OUTLET.
- ✓ EPA COMPLIANT TO IEC 61340-5-1
- ✓ EEC MADE TOP QUALITY ELECTRICAL & ELECTRONIC COMPONENTS FOR UTMOST RELIABILITY AND GLOBAL USE.
- ✓ UNIT OVERHEATING PROTECTED & RFI/EMC FILTER EQUIPPED.
- ✓ EASY TO MOVE AROUND THANKS TO LOW MOTOR MOUNT, WHEEL WELL PROTECTED CASTOR AND ROBUST REAR WHEELS.
- ✓ 10 METERS DETACHABLE SCHUKO OR FUSED UK PLUG CORDSET. 15 METERS ACTION RANGE.
- ✓ LIFT OFF WING SHAPED QUICK STORAGE CORDSET HOLDER.

MAX. MOTOR POWER : 1100W 50/60 hz
MAX. VACUUM POWER : 210 mbar
MAX. AIRFLOW : 45 L/Sec
NOISE LEVEL : 64 db



MEASUREMENTS : 39 x 34 x 42,5 CM (LxWxH). WEIGHT : 6 KG (APPLIANCE)

MUNTZ 888-ESD-S GS


- ✓ EPA HOSE ASSEMBLY EXTENDING FULL 3 METERS !
- ✓ METAL BEND HANDLE C/W AIR REGULATOR, STEEL MINI EXTENSION TUBE SET AND WHEELED FLOOR/BRUSH TOOL FOR FLOORS, WALLS AND CEILINGS.
- ✓ CREVICE NOZZLE, FLEXIBLE RUBBER NOZZLE AND D-SHAPE BRUSH NOZZLE FOR DETAILED CLEANING.
- ✓ 12 L FILTERBAG CAPACITY. UNIT AVAILABLE IN TWO CLEANROOM ISO 14644-1 FILTER SET-UP'S.
- ✓ OVERSIZED MOTORFILTER ENSURES STEADY AIR-FLOW EXTENDING BOTH MOTOR & FILTER LIFE. ELIMINATES PREMATURE CLOGGING.
- ✓ OPTIONAL BLOW ASSEMBLIES TURN UNIT INTO A VERY POWERFUL BLOWER. A GREAT ALTERNATIVE TO COMPRESSED OR COSTLY CANNED AIR (GAS DUSTERS).
- ✓ 100V & 120V VERSIONS AVAILABLE.

ISO 7

MT-853 HEPA H14*	MT-853 MICROMOTORFILTER (INSIDE)
MT-857 HEPA H14*	MT-857 EXTERNAL AIR EXIT FILTER

ISO 4

MT-853 HEPA H14*	MT-853 MICROMOTORFILTER (INSIDE)
MT-858 ULPA U15*	MT-858 EXTERNAL AIR EXIT FILTER



FILTER CONFIGURATIONS (FILTER SET-UP'S) AVAILABLE :

ISO 7 (CLASS 10.000)

GERMAN "M" CLASS MELTBLOWN FILTERBAG MT-850/MT-851 + HEPA H14 MOTORFILTER MT-853 + HEPA H14 MT-857 EXIT FILTER

ISO 4 (CLASS 10)

GERMAN "M" CLASS MELTBLOWN FILTERBAG MT-850/MT-851 + HEPA H14 MOTORFILTER MT-853 + ULPA U15 MT-858 EXIT FILTER

EPA/CR BlowVac Special Electronic (Silent version)

- ✓ ADDED NOISE ABSORBING MATERIALS.
- ✓ FULL ELECTRONIC STEPLESS CONTROL OF :
 - MOTOR SPEED
 - ELECTRIC CONSUMPTION
 - VACUUM POWER
 - BLOW POWER
 - NOISE LEVEL





MEASUREMENTS : 39 x 34 x 42,5 CM (LxWxH). WEIGHT : 6 KG (APPLIANCE)

MUNTZ 888-ESD-S-E GS

MT-853 HEPA H14*	MT-853 MICROMOTORFILTER (INSIDE)
MT-857 HEPA H14*	MT-857 EXTERNAL AIR EXIT FILTER

MT-853 HEPA H14*	MT-853 MICROMOTORFILTER (INSIDE)
MT-858 ULPA U15*	MT-858 EXTERNAL AIR EXIT FILTER



Manufactured in The Netherlands to European Community Standards No. 2006/95/EC & 2004/108/EC

Hergestellt in Holland nach normen der EG 2006/95/EWG & 2004/108/EWG.

Fabrique en Pays-Bas conformement aux normes de la communauté Européenne 2006/95/CEE & 2004/108/CEE.

Fabricado en Holanda de conformidad con las normas comunitarias Europeas 2006/95/CEE y 2004/108/CEE.

WALBOM A/S

Amager Landevej 246 · DK-2770 Kastrup · Denmark · Tel. +45 32 46 11 60 · walbom@walbom.dk

WWW.WALBOM.DK

MELTBLOWN = Fine weave HEPA-like synthetic microfiber filtermedia.
HEPA = High Efficiency Particulate Air. Retention down to 99.990% on 0.3 µ particles.
ULPA = Ultra Low Penetration Air. Retention down to 99.997% on 0.3 µ particles.

IEC 61340-5-1 = EPA = Electrostatic Protected Area, solely permitting use totally ESD safe materials and production aids to fully protect ESD sensitive electronics against harmful electrostatic discharges.

MUNTZ TECHNIKS BV RESERVES THE RIGHT TO CHANGE, ALTER OR MODIFY ITS APPLIANCES, REPLACEMENT PARTS, ACCESSORIES, OR THEIR PACKAGING, WITHOUT PRIOR NOTICE, EXCEPTING THOSE WITHIN SPECIFIC SUPPLY CONTRACT ARRANGEMENTS.

ACCESSORIES 888 GS EPA/CR BLOWVAC SERIES

FILTER GUIDE (NO LIQUIDS !)

Meltblown (fleece). High level filtration, yet maintains suction power & airflow. Ideal for humidity controlled CR use as permits pick-up moist air and dust.

Activated carbon. Neutralises majority smells & odours. Arrests moist from air.

HEPA = High Efficiency Particulate Air. 99.990% retention on 0.3 µ particles.

ULPA = Ultra Low Penetration Air. 99.997% retention on 0.3 µ particles.

MT-850



Disposable Meltblown filterbag set

MT-851



Disposable Meltblown filterbag set

MT-852



Activated carbon jacket (MT-753 use)

MT-853



HEPA Motorfilter (placed before motor)

MT-857 ESD

HEPA



Exit filter (placed after motor)

MT-858 ESD

ULPA



Exit filter (placed after motor)

MT-888 ISO 7


KIT



1 x MT-851 + MT-853 + MT-857

MT-888 ISO 4

KIT



1 x MT-851 + MT-853 + MT-858

MT-861 ESD

Relaxed = 0.9 m
Extended = 3 m



Original hose assy complete

MT-862 ESD

Relaxed = 2.5 m
Extended = 8.5 m



Super stretch hose assy complete

MT-863 ESD

Relaxed = 1.2 m
Extended = 3 m



Blow assembly + connector

MT-864 ESD

Relaxed = 2.8 m
Extended = 9.1 m




Blow assembly + connector (long version)

BRUSH GUIDE

Brush hardness : ☒ MEDIUM/HARD
☐ MEDIUM
☐ VERY SOFT
(indicative)

PHU-04 ESD



Mini attachment set

PHU-05 ESD



Long soft rubber nozzle

- ☒ PHU-07 ESD
- ☐ PHU-08 ESD
- ☐ PHU-09 ESD



PHU-05 ESD c/w brush head


PHU-22 ESD



Small moulded upholstery nozzle

PHU-23 ESD

ALU



Large aluminium upholstery nozzle

PHU-26 ESD

32 mm



Soft rubber bulk pick up nozzle
L = 150 mm. IID = 32 mm.

PHU-27 ESD



Wheeled swivel action floor nozzle
with strip brushes. Width 330 mm.


PHU-27 ESD

ALU



Swivel action alu floor nozzle with
removable brush. Width 330 mm.

PHU-28 ESD



Fully (both in- and outside) electroplated steel

Special mini extension rod set (3 x rod)

- ☒ PHU-11 ESD
- ☐ PHU-12 ESD
- ☐ PHU-13 ESD

PHU-15 ESD

Round brush nozzle. Conductive
monofilament tufted.

PHU-16 ESD



Crevice nozzle

PHU-19 ESD



Modified PHU-05 ESD
c/w mini crevice nozzle

PHU-20 ESD



Long soft rubber nozzle

WARNING : "ESD" ATTACHMENTS ARE DESIGNED TO FUNCTION IN ESD-SAFE MODE IN EPA ENVIRONMENTS OR WITH EPA VAC'S / BLOWVAC'S CONNECTED TO A PROPERLY EARTHED POWER OUTLET ONLY !